



PARTS DETAIL :-

S No.	PART NAME	MATERIAL	QTY.
1	BODY	CI	1
2	DISC	SS-316	1
3	LINER	EPDM	1
4	STEM	AST A 276 , GR SS410	1
5	BUSH	PTFE / NYLON	3
6	O-RINGS	EPDM / NITRILE	2
7	NOTCH PLATE	M.S (POWDER COATING)	1
8	HANDLEVER	M.S (POWDER COATING)	1
9	FASTENER	SS / MS.	3

HYDROSTATIC TEST PRESSURE	
BODY (Kgf/cm ²)	SEAT (Kgf/cm ²)
24	17.6

SIZE	RATING	VALVE DIMENSIONS									MOUNTING FLANGE DETAIL			
		A	H1	H2	H3	L	ØD	FLANGE STANDARD	FACING	PCD-1	PCD	HOLE DIA	NO. OF HOLES	
DN-40	PN16	33	57	125	28	175	40.5	IS:1538/BS:4505	RAISED FACE	126	50	7	4	
DN-50	PN16	43	62	120	28	175	50.5	IS:1538/BS:4505	RAISED FACE	145	50	7	4	
DN-65	PN16	46	72	130	34	216	65	IS:1538/BS:4505	RAISED FACE	160	50	7	4	
DN-80	PN16	46	76	140	34	216	80	IS:1538/BS:4505	RAISED FACE	180	50	7	4	
DN-100	PN16	52	95	160	39	267	100	IS:1538/BS:4505	RAISED FACE	210	50	7	4	
DN-125	PN16	56	114	170	39	267	123	IS:1538/BS:4505	RAISED FACE	240	70	10	4	
DN-150	PN16	56	126	190	39	267	148.5	IS:1538/BS:4505	RAISED FACE	275	70	10	4	
DN-200	PN16	60	161	230	45	350	197	IS:1538/BS:4505	RAISED FACE	295	70	10	4	
DN-250	PN16	68	215	280	45	350	250.5	IS:1538/BS:4505	RAISED FACE	358	70	12	4	
DN-300	PN16	78	230	310	45	350	299.5	IS:1538/BS:4505	RAISED FACE	429	70	12	4	

SKS VALVES	
CLIENT	
P.O./ENQ. NO.	
Model :	SKS116S6L
GAD No. :	19BFDT0002-02
Face to Face :	BFCONCENTRIC
Valve Type :	
Operator:	Hand Lever
SCALE N.T.S	
SHEET 1 OF 1	

Due to Continuous Development we reserve the rights to change in dimensions & Design keeping standard specification same.

All Dimensions are in MM unless otherwise stated.