



PT No.	Part Name	Material
01	Body	Cast Iron
02	Strainer Mesh	SS 304
03	Gasket	EPDM
04	Cover	Cast Iron
05	Nut & Bolt	Stainless Steel
06	Mesh	3mm Perforated Sheet

Y STRAINER FLANGED			
Size	Face-Face(A)	Flange OD(Φ D)	T
DN25	190 \pm 2	114	7
DN32	194 \pm 2	120	8
DN40	202 \pm 2	133	9
DN50	207 \pm 2	152	9.5
DN65	220 \pm 2	165	10
DN80	265 \pm 2	184	11
DN100	330 \pm 2	215	12.5
DN125	377 \pm 2	254	14
DN150	390 \pm 2	279	17.5
DN200	468 \pm 2	335	19
DN250	535 \pm 2	406	22
DN300	580 \pm 2	457	25.5

Hydrostatic Test Pressure
Body, Kg/cm ²
24

SKS
VALVES

CLIENT	
P.O./ENQ. NO.	
TITLE :	Y STRAINER FLANGED
VALVE TYPE:	Y - TYPE
MATERIAL:	CAST IRON
MODEL:	SKS 274
RATING:	PN 16
SCALE	
N.T.S	
SHEET 1 OF 1	

NOTE : FLANGE DRILLING IS AS PER BS10 TABLE

All Dimensions are in MM unless otherwise stated.

Due to Continuous Development we reserve the rights to change in dimensions & Design keeping standard specification same.